



dLAN® 1200+

Technical data

| | |
|--|---|
| Standards | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3az, IEEE 802.1p Auto MDI/X |
| Protocols | CSMA/CA (Powerline) |
| Transmission speeds | Ethernet 10/100/1000 (mbps) Powerline 200/500/600/1200 (mbps) |
| Modulation • Carrier | Powerline OFDM - 4096/1024/256/64-QAM, QPSK, BPSK • Powerline 2880 |
| Range (in m) | Powerline: 400 |
| Security | 128 Bit AES |
| LEDs | dLAN (multi) |
| Buttons | Pairing |
| Socket • Connector • Countries | Type F (CEE 7/4) • F (CEE 7/4) • (DE, NL, ES, PT, AT, SE, FI, NO, GR, HU) |
| Power output to integrated socket | 16 A |
| Device port | 1 x Ethernet RJ45 |
| Power consumption | Maximum W/A: 4.2 Typical W/A: 3.0 Stand-By W/A: 0.7 |
| Power supply | internal 196-250 V AC 50 Hz |
| Attenuation filter | 2 - 68 MHz |
| Filter characteristics | -22 db to -45 db |
| Temperature (Storage • Operating) | -25°C to 70°C • 0°C to 40°C |
| Dimensions (in mm, without plug) | 130 x 66 x 42 |
| Ambient conditions | 10-90% Humidity (non-condensing) |
| Operating systems | Windows 7 (32 Bit), Windows 7 (64 Bit) Windows 8.x (32 Bit), Windows 8.x (64 Bit), Windows 8.x Pro (32 Bit), Windows 8.x Pro (64 Bit) Ubuntu-Linux 12.04 (32 Bit) MAC OS X 10.6, MAC OS X 10.7, MAC OS X 10.8, MAC OS X 10.9 |
| Certifications | CE Class B (EU, CH, NO) |



dLAN® 1200+

Sales information

| | |
|----------------------------|--|
| Warranty (in years) | 3 |
| Accessories | Printed Install Flyer Ethernet Cable(s) |

Single adapter

9375 (EU)

EAN: 4250059693753
Weight: 380 g
Dimensions: 115 x 190 x 81 mm

WEEE additional information:

Weight WEEE: 255 g
Paper (Green Dot): 100 g
Plastic (Green Dot): 2 g
other (Green Dot): 0.2 g

Starter Kit

9382 (EU)

EAN: 4250059693821
Weight: 710 g
Dimensions: 188.5 x 231 x 78.5 mm

WEEE additional information:

Weight WEEE: 510 g
Paper (Green Dot): 165 g
Plastic (Green Dot): 4 g
other (Green Dot): 0.2 g